

HASON

Model.T7E-P



Introduction :

Weighing Indicator T7E adopts fast speed , high precision A/D conversion technology , widely applied in electronic platform scale, electronic floor scale , and so on alike static weighing system equipped with 1-4 loadcell

Features:

low power consumption, provided with different kinds of power saving mode.

Optional for RS232 communication with selectable baud rate and scoreboard interface sending by 20mA current loop .

Various kind of weighing mode , with easy operation

AC/DC both available , could be recharged during power off .

Basic function

Peak hold function

Animal weighing function

Kg/lb switch function

Pre-set tare weight function

High-ok-low function

Weight accumulate , accumulate display ,accumulate clear fuction

ZERO trucking range , ZERO setting (switch on / manually) range , speed rate of zero setting could be set separately .

Battery indication and alarm for low battery protection .

Parameters:

Input signal range -19mV-19mV

Loadcell excitation: DC5V;

Max. connection number of loadcell: 4 at 350ohm

Loadcell connection mode : 6 wires

Verified counts 3000

Display 6 digits LED,6status indications

Display range -999999-999999

Power supply : AC 220v : 50-60hz DC In-built rechargeable battery

Capacity : 15/30/60/100/150/200/300/500/600/750/1000 Kg.

Platform size : 30x30/30x40/40x50/50x60/60x80/80x80/100x100 cm.

Dealer/After sales service :