

HASON

WI-P series

เครื่องชั่งดิจิตอลพร้อมปริ้นเตอร์ในตัว



Specification

Display	: 20 mm high 6 digit 7 - segment
Display Resolution	: 1 parts in 100,000
Internal Resolution	: 1 parts in 1,048,000
Display Increment	: 1, 2, 5, 10
Decimal Point	: 0 to 4 place
Input Signal Range	: 0 to 20 mV
Load Cell Excitation	: 5 Vdc upto 8x350 Ohm load cells
Operation	: -10 to +40 degrees C
Power Requirement	: 220 Vac 50-60 Hz
Data Output	: One channel RS-232 port
Printer Type	: internal printer
Label Roll Dimension	: outside diameter 32 mm
Label Paper Width	: 44 mm
Printer Speed	: 1 line/second
Callibration	: Front panel digital calibration
Dimensions	: 235 mm x 45 mm x 485 mm

BATCH	1
DATE	02/03/51
TIME	09:47
GROSS	92.5 KG.
TARE	16.0 KG.
NET	76.5 KG.
DATE	02/03/51
TIME	09:47
GROSS	86.3 KG.
TARE	16.0 KG.
NET	70.3 KG.
TOTAL	2 Pcs
GROSS	178.8 KG.
TARE	32 KG.
NET	146.8 KG.

Description

Weight Indicator with Internal Printer

Suitable for bench/floor scale applications

Proportional tare

RS-232 communication

Update the date and time automatically with the

Direct internal print (continuous roll jurnal paper)

Printer : date, time, gross, tare, net, total (piece,

*ขนาดแท่นชั่ง พิกัด และค่าความละเอียดตามที่ลูกค้ากำหนด