

WALL SAWING

เครื่องตัดกำแพง “ทีโรลิต” (TYROLIT)



DZ-S2



WZ



FZ-2ST



FZ-4S



CSF-50

Model	DZ-S2	WZ	FZ-2ST	FZ-4S	CSF-50
KT Code					
SAW BLADE					
Max. cutting depth	510mm	710mm	710mm	1005mm	-
Max.saw bladeØ	1,200mm	1600mm	1600mm	2200mm	-
Free detachable up to Ø	900mm	825mm	1025mm	1025mm	-
Blade flange mounting	Central screw	Quick-release flange	Quick-release flange	Quick-release flange	-
Saw blade fixing (flush cuts)	6 countersunk head screws, 130mm graduated circle	6 countersunk head screws, 130mm graduated circle	6 countersunk head screws, 130mm graduated circle	6 countersunk head screws, 130mm graduated circle	-
BAR					
Cutting depth	-	-	-	-	500mm
Width	-	-	-	-	4.8mm
WEIGHT					
including drive motor and 2 feed motors	34kg	29kg	42kg	47kg	-
with 2 feed motors only	27kg	24kg	34kg	39kg	-
Saw head with chain	-	-	-	-	12kg
Chassis	-	-	-	-	22kg
ราคา	855,500.-	Call	Call	Call	Call

WALL SAWING (Diamon Tools) ใบตัด

PREMIUM ★ ★ ★
High-performance tools for maximum profitability

- New wall saws for construction professionals
- Based on the successful TYRREX technology
- Improved all-round and optimized for demanding applications

Maximum performance

- Up to 30% higher performance with the same service life, particularly in difficult operating conditions and with high reinforcement ratios
- New turbo segments with excellent slurry removal and improved cooling through reduced lateral friction

Universal use

- Simple selection of suitable wall saws
- Only three types for any challenge - reduced purchase and storage costs

Reliable quality and safety

- Continuous checks of material and production processes form the basis for reliable and safe tools
- Laser-welded segments up to 1200 mm for maximum safety

STANDARD ★ ★
Quality tools for every day use

Convincing performance

- Focused on the requirements of everyday use
- Convincing ratio of speed and service life

Universal use

- Simple selection of suitable wall saws
- Cover a wide range of applications, resulting in reduced purchase and storage costs

Reliable quality and safety

- Made by TYROLIT

Drive	Power	Pressure stages	Power 400V	Weight
PPH20**	20kW	2	32A	140kg
CR-LS	25kW	1	42A	128kg
PPH20***	20kW	4	32A	135kg
PPH20RR***	20kW	4	32A	160kg
PPH25RR***	25kW	4	42A	170kg
AD-S4 RC	30kW	4	44A	210kg
PPH40RR***	40kW	4	60A	238kg

System Combinations

	DZ-S2	WZ	FZ-2ST	FZ-4S	CSF-50
PPH20**	●		+		+
CR-LS	+	●	●		●
PPH20***	+	●	●		●
PPH20RR***	+	●	+		●
PPH25RR***	+	●	●		●
AD-S4 RC	+	+	●	+	●
PPH40RR***			+	●	●

● Recommendation
+ Possible