

AUTO-CUTTER EQUIPPED



2 inch Thermal POS Printer SRP-150



PRODUCT FEATURES

Long-lasting auto-cutter

The Auto-cutter of the SRP-150 has long lifespan up to 1 million cuts. It has specially designed components such as gears, cutting blade and covers to guarantee its lifetime. In addition, it also has a manual button conveniently positioned for easy clearing of the paper jam.



Reliable Auto-cutter

Built-in power supply

The AC / DC adapter is elegantly integrated into the compact printer housing. Consequently, messing around with cables is avoided which is ideal at space-limited POS terminals or highly frequented cash desks.



Built-in Power Supply

Paper Roll Diameter

Print lasts longer with a bigger paper diameter up to Max. Ø 80mm.



Bigger Paper Roll

BR-SRP-150-EN-MAR17-V1-NF

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

PRINT CHARACTERISTICS

Print Method: Direct Thermal
Print Speed: Up to 70 mm/sec
Print Resolution: 203 dpi
Print Width: Up to 48 mm
Sensor: Paper End, Cover Open

MEDIA CHARACTERISTICS

Media Type: Receipt
Media Width: 57.5 mm
Media Roll Diameter: Up to 80 mm
Media Thickness: 0.062 ~ 0.075 mm
Supply Method: Easy Paper Loading

PHYSICAL CHARACTERISTICS

Dimensions (W x L x H): 131 x 164.5 x 124 mm (5.15 x 6.47 x 4.88 inch)
Weight: 1.05 kg (2.31 lbs.)
Power: External Power Adaptor 100-240V AV, 50/60Hz
Drawer Port: 2 ports (via y-type adaptor)

PERFORMANCE CHARACTERISTICS

NV Image Memory: 256 Kbytes (Mono)
Receive Buffer: 4 Kbytes
User Define Buffer: 12 Kbytes
Interface: USB V2.0 HS, Serial

ENVIRONMENT CHARACTERISTICS

Temperature: Operating: 0 ~ 40°C (32 ~ 104°F)
Storage: -20 ~ 60°C (-4 ~ 140°F)
Humidity: Operating: 10 ~ 80% RH
Storage: 10 ~ 90% RH

RELIABILITY

Printer Unit: 20 Million Lines
Thermal Print Head (TPH): 50 km
Auto Cutter: 1.0 Million Cuts

SOFTWARE

Emulation: BXL / POS
Driver: Windows Driver, Linux CUPS Driver, Mac Driver, Utility Program
SDK: Android SDK

FONT / GRAPHICS / SYMBOLOGIES

Character Size: Font A: 12 x 24, Font C: 9 x 24
KOR, CHN, JPN: 24 x 24
Characters Per Line: Font A: 32, Font C: 42
KOR, CHN, JPN: 16

Character Sets: Alphanumeric: 95
Extended Graphics: 128 x 33 page
International: 32

Graphics: Supporting user-defined fonts, graphics, formats, and logos

Barcode Symbologies: 1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D(optional): PDF417, QR code

BIXOLON®

www.Bixolon.com



BIXOLON Co.,Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de