

FISCAL SUGGESTION



3 inch Impact Dot POS Printer SRP-270



The BIXOLON SRP-270 is a high quality and reliable impact dot POS printer (spooler option). The SRP-270 is an ideal printer for point of sale and hospitality applications. The modular user-friendly design, graphics capability, and 4.6 lps print speed offer reliable high performance in a compact, lightweight design. With the fast moving technology of today it is important to have simple integration of peripheral devices. The SRP-270 receipt printer is no exception; drivers are available for Windows and OPOS. Other features of the SRP-270 receipt printer include a paper end sensor that automatically alerts the user when the printer is out of paper, a tear-bar or auto-cutter, and the ability to print one original receipt plus two copies.

BR-SRP-270-EN-MAR17-V1-NF

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

PRINT CHARACTERISTICS

Print Method: 9 Pin / Serial Dot Matrix

Print Speed: Up to 4.6 lps

Print Resolution: 80 dpi (horizontal) / 144 dpi (vertical)

Print Width: Up to 63.5 mm

Sensor: Paper End

MEDIA CHARACTERISTICS

Media Type: Receipt

Media Width: 76.5 mm

Media Roll Diameter: Up to 83 mm

Media Thickness: 0.06 ~ 0.085 mm

Supply Method: Easy Paper Loading

PHYSICAL CHARACTERISTICS

Dimensions (W x L x H): 160 x 249 x 130(A)/149(C)/160(D) mm
(6.29 x 9.80 x 5.11(A)/5.86(C)/6.29(D) inch)

Weight: 2.3 kg (5.07 lbs.)

Power: External Power Adaptor 100-240V AV, 50/60Hz

Drawer Port: 2 ports (via y-type adaptor)

PERFORMANCE CHARACTERISTICS

Memory: 32 Kbit SDRAM, 1 Mbit FlashROM

Receive Buffer: 4 Kbytes

User Define Buffer: 17 Kbytes

Interface: USB V1.1 FS, Serial, Parallel, Ethernet

ENVIRONMENT CHARACTERISTICS

Temperature: Operating: 0 ~ 40°C (32 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

Humidity: Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

RELIABILITY

Printer Unit (MCBF): 18 Million Lines

Thermal Print Head (TPH): 300 Million Dots/Wire

Auto Cutter: 0.5 Million Cuts

SOFTWARE

Emulation: BXL / POS

Driver: Windows Driver, OPOS Driver, Linux CUPS Driver,
Mac Driver, Virtual COM USB/Ethernet Driver, Utility
Program

FONTS / GRAPHICS / SYMBOLOGIES

Character Size: Font A: 9 x 9 Font B: 7 x 9

KOR: 17 x 9 CHN: 16 x 16

Characters Per Line: Font A: 33 Font B: 40

KOR: 20 CHN: 22

Character Sets: Alphanumeric: 95

Extended Graphics: 128 x 7 page

International: 32

Graphics: Supporting user-defined fonts, graphics, formats,
and logos

ACCESSORIES

Optional: Ribbon Cartridge (RRC-201B/RRC-201BR)
B-melodist (RMB-100)

BIXOLON®

www.Bixolon.com



BIXOLON Co.,Ltd.

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de