

# Smart Mobile 4G - L0



## Simple & Easy

- Plug-and-play USB interface

## Smart Operation

- Supports 2G/3G/4G
- Supports real-time signal intensity and operation status monitoring via mobile APP
- Supports data package usage management
- Supports direct connection to 3rd-party monitoring system<sup>1</sup>

## Stable & Reliable

- Supports data encryption for transmission, ensure data safety
- Supports high-speed & reliable 4G transmission, auto-reconnection after data chain breakage

Technical Specification	Smart Mobile 4G-L0
	<b>General Specification</b>
Connection interface	USB
Installation	Plug-and-play, optional for inverter connection
Display	LED indicator
Dimensions (W * H * D)	130 * 50 * 35 mm (5.1 * 2.0 * 1.4 inch)
Weight	79 g (0.2 lb)
Degree of protection	IP65
Power consumption	3.5 W Typical
	<b>Wireless Parameter</b>
Supported standard & carriers	4G / 3G / 2G For supported carries list and more information, please contact local distributors
Sim card type	Mini-sim card (15 mm * 25 mm)
Support system & frequency	4G: LTE FDD 3G: WCDMA / HSDPA / HSUPA / HSPA+ 2G: GSM / GPRS / EDGE For recommended carriers list and details of supported frequencies, please contact local distributors
	<b>Environment</b>
Operating temperature range	-30 °C ~ +65 °C
Operating humidity range	5% RH ~ 95% RH
Storage temperature range	-40 °C ~ +70 °C
Max. operating altitude	4, 000 m (13,123 ft)

The text and figures reflect the current technical state at the time of printing. Subject to technical changes. Errors and omissions excepted. Huawei assumes no liability for mistakes or printing errors. For more information, please visit solar.huawei.com. Version No.01-(20180908)

<sup>1</sup>. 3<sup>rd</sup>-party management system shall match the communication protocol with Huawei Smart Mobile 4G-L0