

# MAX 50~80KTL3 LV

- 6 / 7 MPPTs
- Smart diagnosis
- High efficiency up to 99%
- Local WIFI configuration
- String monitoring
- AC&DC type II SPD
- AFCI protection
- Data storage up to 25 years
- DC side 2 in 1 connection enabled



P O W E R  
- I N G O  
T O M O -  
R R O W O

powering tomorrow  
**Growatt**

[www.ginverter.com](http://www.ginverter.com)

Datasheet	MAX 50KTL3 LV	MAX 60KTL3 LV	MAX 70KTL3 LV	MAX 80KTL3 LV
<b>Input data (DC)</b>				
Max. recommended PV power (for module STC)	75000W	90000W	105000W	120000W
Max. DC voltage			1100V	
Start voltage			250V	
Nominal voltage	585V	585V	600V	600V
MPPT voltage range			200V-1000V	
No. of MPP trackers	6	6	7	7
No. of PV strings per MPP tracker			2	
Max. input current per MPP tracker			26A	
Max. short-circuit current per MPP tracker			32A	
<b>Output data (AC)</b>				
AC nominal power	50000W	60000W	70000W	80000W
Max. AC apparent power	55500VA	66600VA	77700VA	88800VA
Nominal AC voltage(range*)	220V/380V, 230V/400V (340-440V)			
AC grid frequency(range*)	50/60 Hz (45-55Hz/55-65 Hz)			
Max. output current	80.5A	96.6A	112.7A	128.8A
Adjustable power factor	0.8leading ...0.8lagging			
THDI	<3%			
AC grid connection type	3W+N+PE			
<b>Efficiency</b>				
Max. efficiency	98.8%	98.8%	99%	99%
European efficiency	98.4%	98.4%	98.5%	98.5%
MPPT efficiency	99.9%			
<b>Protection devices</b>				
DC reverse polarity protection	Yes			
DC switch	Yes			
DC surge protection	Type II / Type II			
Insulation resistance monitoring	Yes			
AC short-circuit protection	Yes			
Ground fault monitoring	Yes			
Grid monitoring	Yes			
Anti-islanding protection	Yes			
Residual-current monitoring unit	Yes			
String monitoring	Yes			
AFCI protection	Optional			
Anti-PID function	Optional			
<b>General data</b>				
Dimensions (W / H / D)	860/600/300mm			
Weight	82kg	82kg	86kg	86kg
Operating temperature range	-25°C ... +60°C			
Self-consumption	< 1W			
Topology	Transformerless			
Cooling	Smart air cooling			
Protection degree	IP65			
Relative humidity	0-100%			
Altitude	4000m			
DC connection	H4/MC4(Optional)			
AC connection	Cable gland+OT terminal			
Display	LED/WIFI+APP			
Interfaces: RS485 / USB /WIFI/ RF/GPRS	Yes/Yes /Optional/Optional/Optional			
Warranty: 5 years / 10 years	Yes /Optional			
CE , VDE0126, Greece, EN50438, EN50549, C10/C11, UTE C 15-712, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, CEI 0-16, N4105, BDEW, DRRG, TOR Erzeuger G98/G99, G100, AS/NZS3100, AS4777, UNE217001, UNE206007, PO12.2, NRS 097-2-1, MEA , PEA , KSC8565				

\* The AC voltage range and frequency range may vary depending on specific country grid standard.  
All specifications are subject to change without notice.