

TENRYU (THAILAND) CO., LTD.

149/44 Moo 7, Bang Chalong Subdistrict, Bang Phli District, Samut Prakan Province 10540

Tel : +66 2-0058388 Fax : +66 2-0058389 Mobile : +66 64-789-1461

SALES SPECIFICATIONS

Product : R-100
Spec. No. : 01-003-0
Effective Date : 1 April 2018

Description

R-100 is a narrow boiling range, medium evaporating solvent widely use in the painting industry, where high solvency is required.

Specification

<u>Properties</u>	<u>Unit</u>	<u>Test Medthod</u>	<u>Value</u>
Colour (Saybolt)		ASTM D156	25 min
Density @ 15°C	g/ml	ASTM D4052	0.860 – 0.890
Distillation, IBP	°C	ASTM D1078	150 min
Distillation, DP	°C	ASTM D1078	185 max
Aromatic Content.	% vol	GLC Method	99.0 min

Typical Properties

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Appearance	C&B	Visual	Clear & Bright
Water Content	% m/m	ASTM D1364	0.05 max

Application

R-100 is used in the rubber, textile and chemical process industries, and in household products, surface coatings, printing inks, cleaners, and pesticide and wood preservative formulations.

Note : The Company reserves the right to change the information contained herein without notice.