

TENRYU (THAILAND) CO., LTD.

149/44 Moo 7, Bang Chalong Subdistrict, Bang Phli District, Samut Prakan Province 10540

Tel : +66 2-0058388 Fax : +66 2-0058389 Mobile : +66 64-789-1461

SALES SPECIFICATIONS

APC Product : R-150
APC Spec. No. : 01-004-0
Effective Date : 1 April 2018

Description

R-150 is a medium solvent widely used in the painting industry where high solvency is required.

Specification

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Colour (Saybolt)		ASTM D156	22 min
Density @ 15°C	g/ml	ASTM D4052	0.879 – 0.910
Distillation, IBP	°C	ASTM D1078	174 min
Distillation, DP	°C	ASTM D1078	216 max

Typical Properties

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Aromatic Content	% vol	ASTM D1319	99.0 min
Flash Point	°C	ASTM D56	55 min
Copper Corrosion		ASTM D130	Pass
Density @ 20 °C	g/ml	ASTM D4052	0.870 - 0.900

Application

R-150 is used in the chemical process industries, and surface coatings, printing inks, cleaners, and wood preservative formulations.

Note : The Company reserves the right to change the information contained herein without notice.