# TENRYU (THAILAND) CO., LTD.

149/44 Moo 7, Bang Chalong Subdistrict, Bang Phli District, Samut Prakan Province 10540

Tel: +66 2-0058388 Fax: +66 2-0058389 Mobile: +66 64-789-1461

## SALES SPECIFICATIONS

**Product**: Acetone

**Spec. No.** : 02-001-0

Effective Date : 1 April 2018

#### Description

Acetone is the lowest molecular weight member of the ketone family of solvents, low boiling, fast evaporating, colourless and stable liquid.

Acetone have possesses excellent solvent power for most natural and synthetic resins including acrylics, vinyl polymers, nitrocellulose, cellulose acetate, and other cellulose derivatives, it is a popular and effective low-boiling solvent for surface coating applications.

Since most waxes, oils, fats, grease and dye materials are soluble in acetone, it is ideally suitable for extraction media and other end uses.

#### Specification

| <u>Properties</u>         | <u>Unit</u> | Test Medthod | <u>Value</u> | <u> </u> |
|---------------------------|-------------|--------------|--------------|----------|
| Purity                    | % wt        | GC           | 99.5         | min      |
| Colour (Pt-Cobalt)        |             | ASTM D1209   | 5            | max      |
| Water Content             | % m/m       | ASTM D1364   | 0.50         | max      |
| Distillation, IBP         | °C          | ASTM D1078   | 1.0          | max      |
| Distillation, DP          | °C          | ASTM D1078   | Includi      | ng 56.1  |
| Acidity as acetic acid    | % m/m       | ASTM D1613   | 0.002        | max      |
| Permanganate time @ 25 °C | minutes     | ASTM D1363   | 30           | min      |

### **Typical Properties**

| <u>Properties</u>   | <u>Unit</u> | <b>Test Method</b> | <u>Value</u>  |
|---------------------|-------------|--------------------|---------------|
| Density @ 20 °C     | g/ml        | ASTM D4052         | 0.789 - 0.793 |
| Water Miscibility   |             | ASTM D1722         | pass          |
| Non-volatile matter | g/100ml     | <b>ASTM D1353</b>  | 0.001 max     |

#### **Application**

Acetone finds application in the manufacture of acetone rayon, photographic films, smokeless powder, artificial leather, dopes, cements and paint remover and as absorbent for compressed acetylene.

A large quantity of acetone also serves as a raw material and/or intermediate in the production of other chemicals, such as methacrylate resins, pharmaceuticals, bisphenol A and solvents. Application for acetone as a solvent include printing inks, adhesives cleaning and pharmaceuticals and in solvent extraction from seeds, bones and fish.

Note: The Company reserves the right to change the information contained herein without notice.