

TENRYU (THAILAND) CO., LTD.

149/44 Moo 7, Bang Chalong Subdistrict, Bang Phli District, Samut Prakan Province 10540

Tel : +66 2-0058388 Fax : +66 2-0058389 Mobile : +66 64-789-1461

SALES SPECIFICATIONS

Product : IPAL
Spec. No. : 03-006-0
Effective Date : 1 April 2018

Description

IPAL is a mixture of isopropyl alcohol and ethanol.

Specification

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Colour (Pt-Cobalt)		ASTM D1209	10 max
Density @ 20 °C	g/ml	ASTM D4052	0.784 - 0.793
Water Content	% m/m	ASTM D1364	0.2 max
Alcohol Content	% wt	GC	99.5 max

Typical Properties

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Distillation, IBP	°C	ASTM D1078	81.0 min
Distillation, DP	°C	ASTM D1078	83.5 max

Application

IPAL is a solvent for Lacquers, Thinners, Latex Rubber and Liquid Printing Inks.

Note : The Company reserves the right to change the information contained herein without notice.