

TENRYU (THAILAND) CO., LTD.

149/44 Moo 7, Bang Chalong Subdistrict, Bang Phli District, Samut Prakan Province 10540

Tel : +66 2-0058388 Fax : +66 2-0058389 Mobile : +66 64-789-1461

SALES SPECIFICATIONS

Product : Ethyl Acetate
Spec. No. : 04-001-0
Effective Date : 1 April 2018

Description

Ethyl acetate is a low-boiling ester with a pleasant non-residual odour, miscible with many organic solvents. It is an excellent solvent for cellulose esters.

Specification

<u>Properties</u>	<u>Unit</u>	<u>Test Method</u>	<u>Value</u>
Purity	% m/m	GC	99.0 min
Colour (Pt-Cobalt)		ASTM D1209	10 max
Density @ 20 °C	g/ml	ASTM D4052	0.897 - 0.904
Water Content	% m/m	ASTM D1364	0.10 max
Distillation, IBP	°C	ASTM D1078	75.0 min
Distillation, DP	°C	ASTM D1078	78.0 max
Acidity as acetic acid	% m/m	ASTM D1613	0.01 max

Application

Ethyl acetate is widely used as a solvent in the surface coatings, adhesives, printing inks and other industries.
It is a solvent for nitrocellulose, acrylics, polyurethane, chlorinated rubber and vinyl.

Note : The Company reserves the right to change the information contained herein without notice.