TENRYU (THAILAND) CO., LTD.

149/44 Moo 7, Bang Chalong Subdistrict, Bang Phli District, Samut Prakan Province 10540

Tel: +66 2-0058388 Fax: +66 2-0058389 Mobile: +66 64-789-1461

SALES SPECIFICATIONS

Product: N-Butyl Acetate

Spec. No. : 04-002-0

Effective Date : 1 April 2018

Description

Normal Butyl Acetate is a medium-boiling ester with a characteristic odour, miscible with many organic solvents.

Specification

<u>Properties</u>	<u>Unit</u>	Test Medthod	<u>Value</u>
Purity	% m/m	GC	99.0 min
Colour (Pt-Cobalt)		ASTM D1209	10 max
Density @ 20 °C	g/ml	ASTM D4052	0.879 - 0.883
Water Content	% m/m	ASTM D1364	0.10 max
Distillation, IBP	°C	ASTM D1078	122.0 min
Distillation, DP	°C	ASTM D1078	129.0 max
Acidity as acetic acid	% m/m	ASTM D1613	0.03 max

Application

Normal Butyl Acetate finds applications in surface coatings base on nitrocellulose, cellulose ethers and urethanes. It is also used as an extraction solvent in many areas of industry.

Note: The Company reserves the right to change the information contained herein without notice.