

Maximum Working Pressure : 31.0MPa / 4,500PSI




Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight			
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
HQ3508-77	1/2	12.7	0.88	22.4	5,000	34.5	20,000	138.0	4.72	120	0.50	750	4S	UB
HQ3510-77	5/8	15.9	1.05	26.6	5,000	34.5	20,000	138.0	6.30	160	0.66	990		
HQ3512-77	3/4	19.0	1.15	29.2	5,000	34.5	20,000	138.0	7.87	200	0.72	1,080		
HQ3516-77	1	25.4	1.45	36.9	5,000	34.5	20,000	138.0	9.45	240	1.30	1,950		
HQ3520	1-1/4	31.8	1.93	49.0	5,000	34.5	20,000	138.0	12.99	330	2.49	3,730	6S	UZ

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to +212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

4S

4 spiral wires



6S

6 spiral wires

