

**Maximum Working Pressure : 20.5MPa / 3.000PSI**



Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
PF2104	1/4	6.3	0.51	12.9	3,000	20.5	12,000	82.0	1.97	50	0.13	200	1W	UZ
PF2106	3/8	9.5	0.67	16.9	3,000	20.5	12,000	82.0	2.56	65	0.28	420	2W	UB
PF2108	1/2	12.7	0.80	20.4	3,000	20.5	12,000	82.0	3.35	85	0.35	530		
PF2110	5/8	15.9	0.98	24.9	3,000	20.5	12,000	82.0	3.94	100	0.47	710		
PF2112	3/4	19.0	1.13	28.7	3,000	20.5	12,000	82.0	4.72	120	0.61	910		
PF2116	1	25.4	1.41	35.8	3,000	20.5	12,000	82.0	7.09	190	0.83	1,250		

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to+212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to+158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

**Reinforcement**

**1W**  
1 wire braid

**2W**  
2 wire braids