









Maximum Working Pressure : 14.0MPa / 2,000PSI

BRIDGESTONE PA1404

Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
PA1404	1/4	6.3	0.54	13.6	2,000	14.0	8,000	56.0	2.17	55	0.16	240	1W	UZ
PA1406	3/8	9.5	0.65	16.6	2,000	14.0	8,000	56.0	2.95	75	0.23	350		UB
PA1408	1/2	12.7	0.77	19.5	2,000	14.0	8,000	56.0	3.54	80	0.27	400		
PA1410	5/8	15.9	0.99	25.2	2,000	14.0	8,000	56.0	4.72	110	0.50	750	2W	
PA1412	3/4	19.0	1.16	29.5	2,000	14.0	8,000	56.0	5.51	130	0.63	940		
PA1416	1	25.4	1.41	35.8	2,000	14.0	8,000	56.0	7.09	175	0.82	1,230		
PA1420	1-1/4	31.8	1.71	43.5	2,000	14.0	8,000	56.0	9.45	220	1.07	1,610		UZ
PA1424	1-1/2	38.1	2.07	52.7	2,000	14.0	8,000	56.0	11.02	270	2.04	3,060	4S	HW
PA1432	2	50.8	2.60	66.0	2,000	14.0	8,000	56.0	14.57	370	2.77	4,150		

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to +212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

