









Maximum Working Pressure : 27.5MPa / 4,000PSI

BRIDGESTONE PA2804

Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
PA2804	1/4	6.3	0.59	15.1	4,000	27.5	16,000	110.0	2.76	70	0.25	380	2W	UZ
PA2806	3/8	9.5	0.75	19.1	4,000	27.5	16,000	110.0	3.94	100	0.36	540		UB
PA2808-77	1/2	12.7	0.90	22.8	4,000	27.5	16,000	110.0	4.33	110	0.52	780	4S	
PA2810-77	5/8	15.9	1.06	26.8	4,000	27.5	16,000	110.0	5.51	140	0.67	1,000		
PA2812-77	3/4	19.0	1.17	29.6	4,000	27.5	16,000	110.0	6.69	170	0.75	1,130		
PA2816-77	1	25.4	1.44	36.7	4,000	27.5	16,000	110.0	8.66	220	1.17	1,750		
PA2820	1-1/4	31.8	1.79	45.5	4,000	27.5	16,000	110.0	11.02	280	1.74	2,610		UZ
PA2824	1-1/4	38.1	2.20	55.9	4,000	27.5	16,000	110.0	12.60	320	2.93	4,390	6S	KN
PA2832	2	50.8	2.95	75.0	4,000	27.5	16,000	110.0	16.93	430	5.27	7,900		KD

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°F to +100°F (-40°F to +212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

