









Maximum Working Pressure : 3.5MPa / 500PSI



Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
PA0304	1/4	6.3	0.55	14.0	500	3.5	2,000	14.0	2.17	55	0.10	150	4C	UL
PA0306	3/8	9.5	0.69	17.4	500	3.5	2,000	14.0	2.56	65	0.14	210		
PA0308	1/2	12.7	0.84	21.3	500	3.5	2,000	14.0	3.54	90	0.19	280		
PA0310	5/8	15.9	0.93	23.5	500	3.5	2,000	14.0	4.33	110	0.20	300	2C	
PA0312	3/4	19.0	1.24	31.4	500	3.5	2,000	14.0	5.31	135	0.39	590	4C	
PA0316	1	25.4	1.48	37.5	500	3.5	2,000	14.0	6.69	170	0.49	740		
PA0320	1-1/4	31.8	1.64	41.7	500	3.5	2,000	14.0	7.87	200	0.77	1,150	1W	UT
PA0324	1-1/2	38.1	1.90	48.3	500	3.5	2,000	14.0	9.84	250	0.90	1,350		LC

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to +212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

