









Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
PA0704	1/4	6.3	0.52	13.2	1,000	7.0	4,000	28.0	2.17	55	0.15	220	1W	UZ
PA0706	3/8	9.5	0.64	16.2	1,000	7.0	4,000	28.0	2.95	75	0.22	330		UB
PA0708	1/2	12.7	0.75	19.0	1,000	7.0	4,000	28.0	3.15	80	0.25	380		
PA0710	5/8	15.9	0.93	23.6	1,000	7.0	4,000	28.0	4.33	110	0.34	510		
PA0712	3/4	19.0	1.04	26.5	1,000	7.0	4,000	28.0	5.12	130	0.40	600		
PA0716	1	25.4	1.32	33.5	1,000	7.0	4,000	28.0	6.89	175	0.57	850		
PA0720	1-1/4	31.8	1.71	43.5	1,000	7.0	4,000	28.0	8.66	220	1.07	1,610	2W	UZ
PA0724	1-1/2	38.1	1.98	50.2	1,000	7.0	4,000	28.0	10.63	270	1.27	1,910		HW
PA0732	2	50.8	2.50	63.4	1,000	7.0	4,000	28.0	13.78	350	1.66	2,490		

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to +212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

