









Maximum Working Pressure : 10.5MPa / 1,500PSI

BRIDGESTONE PA1004

Catalog Number														
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight		Reinforcement	Coupling Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
PA1004	1/4	6.3	0.53	13.4	1,500	10.5	6,000	42.0	2.17	55	0.15	230	1W	UZ
PA1006	3/8	9.5	0.65	16.4	1,500	10.5	6,000	42.0	2.95	75	0.23	340		UB
PA1008	1/2	12.7	0.76	19.2	1,500	10.5	6,000	42.0	3.15	80	0.26	390		
PA1010	5/8	15.9	0.94	23.8	1,500	10.5	6,000	42.0	4.33	110	0.35	530		
PA1012	3/4	19.0	1.06	26.8	1,500	10.5	6,000	42.0	5.12	130	0.41	610		
PA1016	1	25.4	1.33	33.8	1,500	10.5	6,000	42.0	6.89	175	0.57	860		
PA1020	1-1/4	31.8	1.71	43.5	1,500	10.5	6,000	42.0	8.66	220	1.07	1,610	2W	UZ
PA1024	1-1/2	38.1	1.98	50.2	1,500	10.5	6,000	42.0	10.63	270	1.27	1,910		HW
PA1032	2	50.8	2.60	66.0	1,500	10.5	6,000	42.0	14.57	370	2.77	4,150	4S	

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to +212°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Oil Resistant Synthetic Rubber
Outer Cover	Weather Resistant Synthetic Rubber

Reinforcement

