

# R13A

## SAE 100R13



Catalog Number													PA/EQ Series	
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight			Reinforcement
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m		
R13A12	3/4	19.0	1.26	32.1	5,000	35.0	20,000	140.0	9.45	240	1.07	1,600	4S	HQ3512-77
R13A16	1	25.4	1.52	38.7	5,000	35.0	20,000	140.0	11.81	300	1.50	2,250		HQ3516-77
R13A20	1-1/4	31.8	1.96	49.8	5,000	35.0	20,000	140.0	16.54	420	2.93	4,400	6S	HQ3520
R13A24	1-1/2	38.1	2.26	57.3	5,000	35.0	20,000	140.0	19.69	500	3.20	4,800		EQ3124
R13A32	2	50.8	2.80	71.1	5,000	35.0	20,000	140.0	25.20	640	4.80	7,200		EQ3132

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +121°C (-40°F to +250°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Synthetic Rubber
Outer Cover	Synthetic Rubber

### Reinforcement

