








DIN 4SP



Catalog Number														PA/EQ Series	
	I.D.		O.D.		Max.W.P.		Min.B.P.		Min.B.R.		Weight				Reinforcement
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	lbs/ft	g/m			
4SP06	3/8	9.5	0.84	21.4	6,500	44.5	26,000	178.0	7.09	180	0.55	820	4S		
4SP08	1/2	12.7	0.97	24.6	6,000	41.5	24,000	166.0	9.06	230	0.63	950		HQ3508-77	
4SP10	5/8	15.9	1.11	28.2	5,100	35.0	20,400	140.0	9.84	250	0.80	1,200		HQ3510-77	
4SP12	3/4	19.0	1.27	32.2	5,100	35.0	20,400	140.0	11.81	300	1.07	1,600		HQ3512-77	
4SP16	1	25.4	1.56	39.7	4,100	28.0	16,400	112.0	13.39	340	1.53	2,300		HQ3516-77	
4SP20	1-1/4	31.8	2.00	50.8	3,000	21.0	12,000	84.0	18.11	460	2.13	3,200		PA2120	
4SP24	1-1/2	38.1	2.25	57.2	2,700	18.5	10,800	74.0	22.05	560	2.53	3,800		PA2124	

Compatible Fluid	Mineral Oil
Temperature Range : fluid	-40°C to +100°C (-40°F to +250°F)
Temperature Range : ambient	-40°C to +70°C (-40°F to +158°F)
Inner Tube	Synthetic Rubber
Outer Cover	Synthetic Rubber

Reinforcement



4S
4 spiral wires

