

Steel Wire Braided Hydraulic

SAE 100 R 2 AT / DIN - EN 853 2SN



TUBE :

HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.

REINFORCEMENT :

HIGH TENSILE 2 STEEL WIRE BRAID.

COVER :

OIL, ABRASION AND WEATHER RESISTANT SYNTHETIC RUBBER.

TEMPERATURE RANGE :

-40 ° C - + 100 ° C

APPLICATION :

FOR HIGH PRESSURE HYDRAULIC SYSTEMS IN INDUSTRY AND AGRICULTURE.

PART	HOSE SIZE ID		OD	MAX. WORKING		BURST PRESSURE		PRICE
NO	INCH	DASH	MM	BAR	PSI	BAR	PSI	METRE
U2AT - 04	1/4	04	15.0	400	5800	1600	23200	
U2AT - 06	3/8	06	18.9	330	4800	1320	19140	
U2AT - 08	1/2	08	22.2	275	4000	1100	15950	
U2AT - 10	5/8	10	25.2	250	3625	1000	14500	
U2AT - 12	3/4	12	29.2	215	3100	850	12325	
U2AT - 16	1	16	37.2	165	2400	650	9425	