

# Steel Wire Braided Hydraulic

SAE 100 R 1 AT / DIN - EN 853 1SN



## TUBE :

HYDRAULIC OIL RESISTANT SPECIAL SYNTHETIC RUBBER.

## REINFORCEMENT :

HIGH TENSILE STEEL WIRE BRAID.

## COVER :

OIL, ABRASION AND WEATHER RESISTANT SYNTHETIC RUBBER.

## TEMPERATURE RANGE :

-40 °C - + 100 °C

## APPLICATION :

FOR HIGH PRESSURE HYDRAULIC SYSTEMS IN  
INDUSTRY AND AGRICULTURE.

PART		HOSE SIZE ID		OD	MAX. WORKING		BURST PRESSURE		PRICE
NO	INCH	DASH	MM	BAR	PSI	BAR	PSI	METRE	
U1AT - 04	1/4	04	13.2	225	3265	900	13050		
U1AT - 06	3/8	06	17.2	180	2610	720	10440		
U1AT - 08	1/2	08	20.4	160	2320	640	9280		
U1AT - 10	5/8	10	23.5	130	1885	520	7540		
U1AT - 12	3/4	12	27.5	105	1525	420	6090		
U1AT - 16	1	16	35.4	88	1276	350	5075		