

# Steel Wire Braided Hydraulic

DIN -EN 856 4SP

High Abrasion Resistant Cover



## TUBE :

MINERAL VEGETABLE HYDRAULIC OILS AND GLYCOL BASIS FLUIDS  
RESISTANT SPECIAL SYNTHETIC RUBBER.

## REINFORCEMENT :

4 HIGH TENSILE STEEL SPIRALS.

## COVER :

OIL,SUPER HIGH ABRASION AND WEATHER RESISTANT H.A.R.C. COMPOUND.

## TEMPERATURE RANGE :

-40 ° C - + 100 ° C

## APPLICATION :

FORHYDRAULIC SYSTEMS WITH HIGH PEAK  
PRESSURES AND ARDUOUS CONDITIONS  
OF OPERATIONS.

PART NO	HOSE SIZE ID		OD	MAX. WORKING		BURST PERSSURE	
	INCH	DASH	MM	BAR	PSI	BAR	PSI
4SP-06	3/8"	06	21.2	460	6670	1780	25810
4SP-08	1/2"	08	24.4	425	6160	1660	24070
4SP-10	5/8"	10	28.0	400	5800	1400	20300
4SP-12	3/4"	12	32.0	380	5510	1400	20300
4SP-16	1"	16	39.1	320	4640	1120	16240