

Water Suction & Discharge Hose



Model: WSD150

INTER WSD150 – WATER SUCTION & DISCHARGE HOSE – WP 150 PSI

Application

For suction / discharge of water and other non-corrosive liquid.

Tube	Synthetic rubber
Reinforcement	High tensile synthetic fabric with steel helical embedded wire
Cover	Ozone and weather resistant synthetic rubber
Color	Black
Surface	Fabric-wrapped finish, smooth
Operating temperature	-20 C to +80 C
Min. bending radius	6 x ID
Safety factor	3:1
Branding	Blue transfer tape with black text



Product code	ID inch	ID mm	OD mm	WP		BP		Length m	Price (in.Vat) Baht/m
				bar	PSI	bar	PSI		
BS-41001	1.1/4	32	45.0	10	150	30	450	40	740.00 *
BS-41002	1.1/2	38	52.0	10	150	30	450	40	815.00 *
BS-41003	2	51	67.0	10	150	30	450	40	845.00 *
BS-41004	2.1/2	63	79.0	10	150	30	450	40	1,220.00 *
BS-41005	3	76	92.0	10	150	30	450	40	1,375.00 *
BS-41006	3.1/2	90	106.0	10	150	30	450	40	1,815.00 *
BS-41007	4	102	118.0	10	150	30	450	40	2,085.00 *
BS-41008	5	127	153.0	10	150	30	450	20	3,350.00 *
BS-41009	6	152	177.0	10	150	30	450	20	4,235.00 *
BS-41010	8	203	239.0	10	150	30	450	15	7,510.00 *
BS-41011	10	254	290.0	10	150	30	450	10	11,475.00 *