Panasonic CONNECT

VIDEO WALL DISPLAY VF SERIES













Key Features

- The VF Series delivers seamless, multi-screen Displays for dynamic, large-screen use
- Ultra narrow bezels on the VF31 series video wall reduce bezel-to-bezel distance to a near-invisible 0.88mm
- Durable panel material and quality components ensures dependable 24 hours operation seven days a week



TH-55VF11

01

TH-55VF21

02

TH-55VF31

03

VIDEO WALL DISPLAY VF SERIES











		TH-55VF31	TH-55VF21	TH-55VF11
Screen size (diagonal)		55-inch (1388 mm) / 16:9		
Panel Type /Backlight		IPS/Direct LED		
Resolution		1920 x 1080		
Brightness		500 cd/m ²		
Contrast ratio		1100:1	1000:1	1200:1
Viewing angle (CR>10)			178° (H) / 178° (V)	
Panel Surface Treatment		Anti-Glare (Haze 28%)	Anti-Glare (Haze 28%)	Anti-Glare (Haze 3%)
Terminals	DP IN	DP 1.2 x 1		
	HDMIIN	HDMI TYPE A Connector x 2		
	PC IN	D-sub 15-pin x 1		
	DVI IN	DVI-D 24-pin x 1		
	AUDIO IN	Stereo Mini Jack(M3) x 1(Shared with PC in)		
	DVI-D OUT	DVI-D 24-pin x 1		
	AUDIO OUT	Stereo Mini Jack(M3) x 1		
	USB	USB Connector (Type A) 2.0 x 1		
	OPS	-		
	LAN	RJ45 x 1, Only for PJ Link		
	RS232C IN/OUT	RJ45 x 1 / RJ45 x 1		
	SDIIN	-		
	SDIOUT	-		
Built-in speaker		-		
Power requirements		100V-240V AC, 50/60Hz		
Power consumption		240 W	165 W	165 W
Standby condition		Approx. 0.5 W		
Dimensions (W x H x D)		1210.5 x 681.2 x 112.1 mm	1212.2 x 683.0 x 97.5 mm	1213.6 x 684.4 x 105.1 mm
Bezel to Bezel		0.88mm	1.8mm	3.5mm
Weight (Display only)		Approx. 27.0 kg	Approx. 27.0 kg	Approx. 30.0kg
Wall-hanging pitch		600 x 400 mm		
		VESA Compliant		
Operating environment		Temperature 0 to 40 deg		
Orientation		Landscape/Portrait (Clockwise)		
Longest use (hours/day)		24/7		

Panasonic CONNECT