



Each Pixel Captivates for Every View

Hikvision LCD Video Wall Display Mirror Series



HIKVISION[®]



EACH PIXEL CAPTIVATES FOR EVERY VIEW

Hikvision's new Mirror Series LCD Displays provide users with versatile, flexible collaboration tools, powerfully designed for a host of everyday scenarios - from board rooms to ball rooms, from lecture halls to shopping malls, and so much more. Hikvision LCD Displays captivate you with every pixel, harnessing the power of our superb technologies such as better color uniformity, high brightness, and pixel-level color calibration, all integrated into a slim unit with a tiny bezel. With cutting edge tech and expansive usability, Hikvision LCDs will meet every display need you can imagine.

WHAT MAKES THE MIRROR SERIES LCDS SO OUTSTANDING?



◀ Up to 30 pieces Daisy Chain ▶

Clutter-free daisy chain

Hikvision LCDs support clutter free daisy chain on up to 30 pieces, along with 4K resolution for superior and economical video walls. Since there are no video splitters, users can connect the LCD screens together using common video and network cables. The displays will be spliced into a holistic view.

Variable display modes

Hikvision LCDs offer three great display modes to present captivating viewing every time, all the time, by adjusting and optimizing parameters in line with a variety of display scenes. Wherever you go, vivid images will be there with you, too.

◀ 3 Display Modes ▶



Monitoring Mode

Enhanced image restoration, frame rates, and gray scale.



Presentation Mode


Better display consistency, text clarity, and smooth text edges.



Movie Mode

Improved color saturation and image contrast.

- 1 Take test picture
- 2 Analyze pixel color
- 3 Generate calibration parameters
- 4 Write data to chip
- 5 Color well calibrated



◀ Precise Color Calibration ▶


True-to-life display

Precise color calibration brings you true-to-life colors and just the right brightness using pixel-by-pixel analysis. Flawless uniformity of color and brightness guarantees Hikvision's LCDs outstanding display performance.

KEY FEATURES

Razor-thin bezels at 0.44mm

Hikvision LCDs support extremely thin 0.44mm even bezel. Such narrow seams present content beautifully and uniformly.



Superb 4K chip

Hikvision's LCDs use the industry-leading NOVATEK NT68400 chip for 4K signal source analysis and ultra-high-definition display.



Flexible rotation

With standard installation, Hikvision LCDs also support 90-, 180-, and 270-degree display rotation, as well as vertical screen splicing without a video wall controller.



EMC class B certification

Advanced design and manufacturing techniques empower Hikvision LCDs with high performance electro-magnetic protection, ensuring a better viewing experience.




Reduced haze and glare

Hikvision LCDs limit haze by up to 28%, which can effectively reduce specular reflection to sustain stress-free visual enjoyment.



KEY FEATURES



Effective heat dissipation

With intelligent temperature control, Hikvision LCDs let users preset the temperature threshold. Fan cooling begins automatically when temperatures reach the threshold. Stable performance and longer lifespan get a big boost.



Lifelike viewing from any angle

The 178-degree viewing angle offers more installation flexibility, providing a wealth of space to present clear imaging wherever your viewer is standing.




All-day operation

Hikvision LCDs' industrial grade panels can run uninterrupted 24/7, promoting your content absolutely any hour you need it.



Industry-leading color calibration

With industrial camera inspection, professional color contrast, and an intelligent pixel-level calibration algorithm, Hikvision LCDs present flawless color consistency and dazzling imaging on every screens.




Durable protection

Hikvision LCDs feature highly corrosion-proof brackets and quality construction for enhanced durability & protection. Moreover, clear wiring on the back side brings more convenience to installation and maintenance.

APPLICATION SCENARIOS



Command Centers / Monitoring Center




Commercial Displays



Conference Rooms

SUPERIOR FEATURES

Centralized Advertising Management



The multifunctional platform, HikCentral FocSign, enhances efficiency in ad making, enabling central management and remote maintenance functions that greatly improve operational efficiency and reduce labor costs.



Creativity on Display



The LCDs can be creatively spliced into various shapes to show more dazzling content, offering more versatile space for designers and visual impact to customers.

SPECIFICATIONS

Models		DS-D2046LU-Y	DS-D2049LU-Y	DS-D2055LU-Y	DS-D2055HU-Y
Image					
		46"	49"	55"	55"
Display Specifications	Sizes (Diagonal)	46"			
	Backlight	LED Backlight (Direct Type)			
	Panel	IPS			
	Resolution	1920 x 1080			
	Number of Colors	16.7 Million			
	Viewing Angles	Horizontal : 178 degrees, Vertical: 178 degrees			
	Response Time	8 ms (G to G)			
	Contrast Ratio	1,200:1			
	Brightness	500 nits	500 nits	500 nits	700 nits
	Pixel Pitch (H x V)	0.53 x 0.53 mm	0.56 x 0.56 mm	0.63 x 0.63 mm	0.63 x 0.63 mm
	Color Saturation	72%			
Surface Treatment	Haze 25%, 3H				
Side Frame Size	Physical Seams	3.5 mm			
Interface	Input Interfaces	VGA x 1, HDMI x 1, DVI x 1, DP x 1, USB x 1			
	Output Interfaces	HDMI x 1			
	Control Interfaces	RS232 In x 1, RS232 Out x 1			
Power	Power Consumption	111 W	134 W	187 W	235 W
	Power Requirements	100 to 240 VAC, 50 or 60 Hz			
Operating Environment	Operating Temperature	0 to 40° C			
	Operating Humidity	10% to 80% (No Condensation)			
	Operating Life	≥ 60,000 Hours			
Physical Features	Dimensions (W x H x D)	1,021.98 x 576.57 x 72.25 mm	1,078.34 x 608.36 x 72.8 mm	1,213.5 x 684.3 x 71.74 mm	1,213.5 x 684.3 x 71.74 mm
	Frame Width	2.3 mm (top/left), 1.2 mm (bottom/right)			

Models		DS-D2055LE-G	DS-D2055HE-G	DS-D2055LR-G	DS-D2055HR-G
Image					
Display Specifications	Sizes (Diagonal)	55"			
	Backlight	LED Backlight (Direct Type)			
	Panel	IPS			
	Resolution	1920 x 1080			
	Number of Colors	1.07 Billion			
	Viewing Angles	Horizontal: 178 degrees, Vertical: 178 degrees			
	Response Time	8 ms (G to G)			
	Contrast Ratio	1,000 : 1		1,100 : 1	
	Brightness	500 nits	700 nits	500 nits	700 nits
	Pixel Pitch (H x V)	0.63 x 0.63 mm			
	Color Saturation	72%			
Surface Treatment	28%, 2H				
Side Frame Size	Physical Seams	1.8 mm		0.88 mm	
Interface	Input Interfaces	VGA x 1, HDMI x 1, DVI x 1, DP x 1, USB x 1			
	Output Interfaces	HDMI x 1			
	Control Interfaces	RS232 In x 1, RS232 Out x 1			
Power	Power Consumption	192 W	230 W	192 W	230 W
	Power Requirements	100 to 240 VAC, 50 or 60 Hz			
Operating Environment	Operating Temperature	0 to 40° C			
	Operating Humidity	10% to 90% (No Condensation)			
	Operating Life	≥ 60,000 Hours			
Physical Features	Dimensions (W x H x D)	1,211.54 x 682.34 x 68.9 mm		1,210.81 x 681.76 x 68.9 mm	
	Frame Width	0.9 mm (top/left), 0.9 mm (bottom/right)		0.44 mm (top/left), 0.44 mm (bottom/right)	



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Business: overseasbusiness@hikvision.com
Technical Support: support@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Azerbaijan
T +994 50 369 81 57
Azerbaijan.CATC@hikvision.com

Hikvision Brazil
T +55-11-3318-0050
Latam.support@hikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

Hikvision Czech
T +420 29 6182640
info.cz@hikvision.com

Hikvision Egypt
T +20223066117
sales.eg@hikvision.com

Hikvision Europe
T +31 23 5542770
sales.eu@hikvision.com

Hikvision France
T +33(0)1 85 330 450
info.fr@hikvision.com

Hikvision Germany
sales.dach@hikvision.com

Hikvision Hong Kong , China
sales.hk@hikvision.com

Hikvision Hungary KFT
info.hu@hikvision.com

Hikvision India
T +91-22-6855 9944
sales@pramahikvision.com

Hikvision Indonesia
T +6221 2933 9366
Sales.Indonesia@hikvision.com

Hikvision Israel
T +972 79 5555590
sales.israel@hikvision.com

Hikvision Italy
T +39 0438 6902
info.it@hikvision.com

Hikvision Kazakhstan
T +7 (727) 291-75-88
support@hikvision.kz

Hikvision Kenya
wangchengbin@hikvision.com

Hikvision Korea
T +82-1661-8138
sales.korea@hikvision.com

Hikvision Malaysia
T +60327224000
sales.my@hikvision.com

Hikvision Mexico
T +52 55 2624 0110
sales.mexico@hikvision.com

Hikvision New Zealand
T 09 217 3127
salesnz@hikvision.com

Hikvision New Panama
Sales.centralamerica@hikvision.com

Hikvision Pakistan
T +92-2135147526
support.pk@hikvision.com

Hikvision Philippines
support.ph@hikvision.com

Hikvision Poland
T +48 22 460 01 50
info.pl@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Romania
marketing.ro@hikvision.com

Hikvision Singapore
T +65 6684 4718
sg@hikvision.com

Hikvision South Africa
T +27 877018113
sale.africa@hikvision.com

Hikvision Spain
T +34 91 737 16 55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Thailand
sales.thailand@hikvision.com

Hikvision Turkey
T +90 216 521 70 70
support.tr@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision UK & Ireland
T +44(0)1628 902 140
info.uk@hikvision.com

Hikvision Uzbekistan
T +998-71-233-55-50
uzbekistan@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Vietnam
T +84 24 7300 7586
sale.vn@hikvision.com

HIKVISION LCD VIDEO
WALL DISPLAY MIRROR SERIES

HIKVISION[®]

Follow us on social media to get the latest product and solution information



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



hikvisionhq



Hikvision Corporate Channel