L-VBM20A ALUMINIUM BIDIRECTIONAL PROJECTION LOUDSPEAKER

- Intelligible voice and superior sound reproduction
- Ceiling or wall mount
- Meets virtually any outdoor requirement
- EN54-24 certified
- Complies with IP65 standard
- Available with or without capacitor(part number without "C")



PRODUCT DESCRIPTION

L-VBM20A/EN is a high-performance 20W voice alarm bidirectional projection loudspeaker. It provides a broad frequency response range, low distortion and high sound pressure level for accurate and intelligible broadcast of evacuation messages and high quality sound reproduction. It can be used in indoor, outdoor, dry, or wet applications, providing reliable operations over wide temperature and humidity ranges.


Bidirectional loudspeaker is the best choice for applications such as tunnel, gallery and shopping arcade. This voice alarm bidirectional projection loudspeaker complies with BS 5859 part8 and EN54 part 24.

Technical Specification	
Max power	30 W
Rated power	20W(10W×2)
Power taps @ 100V	20W/10W/5W/2.5W
SPL at 20W / 1W (100 Hz-10Khz,1m)	99dB/87dB
SPL at 20W / 1W (100 Hz-10Khz,4m)	87dB/75dB
Frequency response (-10 dB)	150 Hz -20 KHz
Rated input voltage	100 V / 70 V


Rated impedance	$500\Omega/1$ K $\Omega/2$ K $\Omega/4$ K Ω
Connector	Fire-resistant cable
Dimensions(D x L)	Ф140 × 195 mm
Weight	3.23 Kg
Color	White(RAL9003)
Material	Aluminum
DC Blocking Capacitor	Yes (2.7uF) L-VBM20A/EN(C)
	No L-VBM20A/EN




Frequency Response




Circuit Diagram



Polar Diagram



Three- View Diagram



For more information,

https://honeywellbuildings.in Call: 1-800-103-0339 Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurgaon - 122 002 ALUMINIUM BIDIRECTIONAL PROJECTION LOUDSPEAKER

Honeywell