

HN-A660 POWER AMPLIFIERS

- 100V, 70V and 4-16 Ohms transformer isolated speaker outputs
- Combination XLR /RCA Line In and Line OUT connectors
- LED status indicators
- Speaker output short circuit protection



PRODUCT DESCRIPTION

These commercial-grade power amplifiers efficiently deliver up to 660 watts of clean, reliable audio for public address applications. They are ruggedly designed to give years of reliable

service. They are equipped with toroidal power transformers, extensive heat-sinking and fan cooling, protective circuits such as over-temperature, short circuit, RFI and soft start.

Technical Specifications

Rated Power	660W
Speaker Output	4~16Ω Low-Z output 660W,70V(7.4Ω) 100V (15.1Ω)
Line Input	<1 V, unbalanced
Line Output	1V unbalanced
Damping Factor	200
Frequency Response	60 Hz~15 kHz (± 3 dB)
THD	< 0.5 % at 1 kHz, 1/3 rated power
S/N	> 80dB
Controls	Volume control and power switch
Cooling	DC12V fan, extensive heat sinking
Indicators	Power, Clip, Signal, Protect and Temp
Power Cable	(3×1.5mm ²)×1.5M(standard)

Protection	AC Fuse × 15 A AC FUSE×1, Current limiter, short circuit and thermal protection circuits
Power Requirement	AC 220 V / 50 Hz
Power Consumption	880W
Dimensions	89 (H) × 483 (W) × 366(D)mm
Packing Dimensions	185 (H) × 520(W) × 435(D)mm
Net Weight	21.36Kg
Gross Weight	19.74Kg

Ordering Information

Description	Ordering Information
Power Amplifiers	HN-A660

For more information,

<https://honeywellbuildings.in>

Call: 1-800-103-0339

Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43,

Block C, Sushant Lok Phase - I,

Gurgaon - 122002